

Product Selection Guide – Access Control Card

Visit <http://www.b-id-us.com> or call 626-821-9128 for more product information

Category		Single Frequency Card					
Product							
Part number		SFC-EM125	SFC-H125	SFC-MF1356-S50	SFC-MF1356-S70	SFC-MF1356-DF	SFC-UHF900
Operating frequency	125KHz	√	√				
	13.56MHz			√	√	√	
	900MHz						√
Format	125KHz	EM	Wiegand-26	-	-	-	-
	13.56MHz	-	-	MiFare Classic 1KB	MiFare 4KB	MiFare DesFire 2K/4K/8K	-
	900MHz	-	-	-	-	-	Alien H2 / H3
Customized FACILITY CODE and ID range		Available**	Available	-	-	-	-
Operating temperature		14°F ~ +122°F (-10°C ~ +50°C)	14°F ~ +122°F (-10°C ~ +50°C)	14°F ~ +122°F (-10°C ~ +50°C)	14°F ~ +122°F (-10°C ~ +50°C)	14°F ~ +122°F (-10°C ~ +50°C)	14°F ~ +122°F (-10°C ~ +50°C)
Application temperature		-13°F ~ +257°F (-25°C ~ +125°C)	-13°F ~ +185°F (-25°C ~ +85°C)	-13°F ~ +185°F (-25°C ~ +85°C)	-13°F ~ +185°F (-25°C ~ +85°C)	14°F ~ +113°F (-10°C ~ +45°C)	14°F ~ +113°F (-10°C ~ +45°C)
Core material		PVC	PVC	PVC	PVC	PVC	PVC
Dimension		85.6 x 54mm	85.6 x 54mm	85.6 x 54mm	85.6 x 54mm	85.6 x 54mm	85.6 x 54mm
Color		White	White	White	White	White	White
Optional services		Please inquire B-Id for any card technology not listed above. Laser ID engraving, color logo printing, hole punch, encoding*, magnetic strip available					

* Product photos / drawings are not actual scale. ** If applicable

Product Selection Guide – Access Control Card

Visit <http://www.b-id-us.com> or call 626-821-9128 for more product information

Category		Dual Frequency Card					
Product							
Part number		DFC-H125MF1356-50	DFC-H125MF1356-70	DFC-E125MF1356-50	DFC-E125MF1356-70	DFC-H125900	DFC-H1356900
Operating frequency	125KHz	√	√	√	√	√	
	13.56MHz	√	√	√	√		√
	900MHz					√	√
Format	125KHz	Wiegand-26	Wiegand-26	EM	EM	Wiegand-26	-
	13.56MHz	MiFare Classic 1KB	MiFare 4KB	MiFare Classic 1KB	MiFare 4KB	-	MiFare 1KB/4KB
	900MHz	-	-	-	-	Alien H2 / H3	Alien H2 / H3
Customized FACILITY CODE and ID range		Available	Available	Available**	Available**	Available	-
Operating temperature		14°F ~ +122°F (-10°C ~ +50°C)	14°F ~ +122°F (-10°C ~ +50°C)	14°F ~ +122°F (-10°C ~ +50°C)	14°F ~ +122°F (-10°C ~ +50°C)	14°F ~ +122°F (-10°C ~ +50°C)	14°F ~ +122°F (-10°C ~ +50°C)
Application temperature		-13°F ~ +257°F (-25°C ~ +125°C)	-13°F ~ +185°F (-25°C ~ +85°C)	-13°F ~ +185°F (-25°C ~ +85°C)	-13°F ~ +185°F (-25°C ~ +85°C)	14°F ~ +113°F (-10°C ~ +45°C)	14°F ~ +113°F (-10°C ~ +45°C)
Core material		PVC	PVC	PVC	PVC	PVC	PVC
Dimension		85.6 x 54mm	85.6 x 54mm	85.6 x 54mm	85.6 x 54mm	85.6 x 54mm	85.6 x 54mm
Color		White	White	White	White	White	White
Optional services		Please inquire B-Id for any card technology not listed above. Laser ID engraving, color logo printing, hole punch, encoding*, magnetic strip available.					

* Product photos / drawings are not actual scale. ** If applicable